



### ALFATORR14 ROOF FANS



Features	Unit	ALFATORRMETB	ALFATORR1450B	ALFATORR1451B
Air flow rate (free blow)	m <sup>3</sup> /h	-	1500/(1550)	
Flow rate with filter fan	m <sup>3</sup> /h	-	900/(950)	
Power supply	V/Hz	-	230-50/60	115-50/60
Dimensions HxWxD	mm	540x390x128	540x390x128	
Power consumption	W	-	160/(215)	
Current consumption	A	-	0.70/(0.98)	1.40/(1.96)
Overcurrent protection	-	-	thermal	
Electric connection	-	-	4-pole terminal	
Duty cycle	-	-	100%	
Operating temperature	°C	-	-20/+50	
Protection degree enclosure side/class	-	-	IP44/Class I	
Noise level	dB(A)	-	74/(75)	
Flow direction	-	-	inside-out	
Bearing	-	-	ball	
Service life (at 40°C)	hr	-	50,000	
Material	-	metal RAL7035		
Gasket	-	PVC	PVC	
Weight (with packaging)	kg	5.2(5.5)	11.3(12.3)	
Package dimensions	mm	550x400x140	550x400x140	
Mounting	-	Screws	Screws	
Conformity/Approvals	-	CE		

#### Versions

RAL7032 - Gray - Code ending	delete B
IP54 - Code ending	F

#### Accessories

Thermostat 0-60°C, NO contact	THV2
Grill with filter mat	ALFA3000BPB
Fan speed controller	FSC
Spare filter mat	ALFAFT15

